

## Environmental Protection Agency

## § 59.406

### § 59.405 Container labeling requirements.

(a) Each manufacturer and importer of any architectural coating subject to the provisions of this subpart shall provide the information listed in paragraphs (a)(1) through (a)(3) of this section on the coating container in which the coating is sold or distributed.

(1) The date the coating was manufactured, or a date code representing the date shall be indicated on the label, lid, or bottom of the container.

(2) A statement of the manufacturer's recommendation regarding thinning of the coating shall be indicated on the label or lid of the container. This requirement does not apply to the thinning of architectural coatings with water. If thinning of the coating prior to use is not necessary, the recommendation must specify that the coating is to be applied without thinning.

(3) The VOC content of the coating as described in paragraph (a)(3)(i) or (a)(3)(ii) of this section shall be indicated on the label or lid of the container.

(i) The VOC content of the coating, displayed in units of grams of VOC per liter of coating or in units of pounds of VOC per gallon of coating; or

(ii) The VOC content limit in table 1 of this subpart with which the coating is required to comply and does comply, displayed in units of grams of VOC per liter of coating or in units of pounds of VOC per gallon of coating.

(b) In addition to the information specified in paragraph (a) of this section, each manufacturer and importer of any industrial maintenance coating subject to the provisions of this subpart shall display on the label or lid of the container in which the coating is sold or distributed one or more of the descriptions listed in paragraphs (b)(1) through (b)(4) of this section.

(1) "For industrial use only."

(2) "For professional use only."

(3) "Not for residential use" or "Not intended for residential use."

(4) "This coating is intended for use under the following condition(s):" (Include each condition in paragraphs (b)(4)(i) through (b)(4)(v) of this section that applies to the coating.)

(i) Immersion in water, wastewater, or chemical solutions (aqueous and nonaqueous solutions), or chronic exposure of interior surfaces to moisture condensation;

(ii) Acute or chronic exposure to corrosive, caustic, or acidic agents, or to chemicals, chemical fumes, or chemical mixtures or solutions;

(iii) Repeated exposure to temperatures above 120° C (250° F);

(iv) Repeated (frequent) heavy abrasion, including mechanical wear and repeated (frequent) scrubbing with industrial solvents, cleansers, or scouring agents; or

(v) Exterior exposure of metal structures and structural components.

(c) In addition to the information specified in paragraph (a) of this section, each manufacturer and importer of any recycled coating who calculates the VOC content using equations 7 and 8 in § 59.406(a)(3) of this subpart shall include the following statement indicating the post-consumer coating content on the label or lid of the container in which the coating is sold or distributed: "CONTAINS NOT LESS THAN X PERCENT BY VOLUME POST-CONSUMER COATING," where "X" is replaced by the percent by volume of post-consumer architectural coating.

[63 FR 48877, Sept. 11, 1998; 64 FR 35001, June 30, 1999]

### § 59.406 Compliance provisions.

(a) For the purpose of determining compliance with the VOC content limits in table 1 of this subpart, each manufacturer and importer shall determine the VOC content of a coating using the procedures described in paragraph (a)(1), (a)(2), or (a)(3) of this section, as appropriate. The VOC content of a tint base shall be determined without colorant that is added after the tint base is manufactured or imported.

(1) With the exception of low solids stains and low solids wood preservatives, determine the VOC content in grams of VOC per liter of coating thinned to the manufacturer's maximum recommendation, excluding the volume of any water and exempt compounds. Calculate the VOC content using equation 5 as follows:

$$\text{VOC Content} = \frac{(W_s - W_w - W_{ec})}{(V_m - V_w - V_{ec})} \quad (5)$$

Where:

VOC content = grams of VOC per liter of coating

$W_s$  = weight of volatiles, in grams

$W_w$  = weight of water, in grams

$W_{ec}$  = weight of exempt compounds, in grams

$V_m$  = volume of coating, in liters

$V_w$  = volume of water, in liters

$V_{ec}$  = volume of exempt compounds, in liters

(2) For low solids stains and low solids wood preservatives, determine the VOC content in units of grams of VOC per liter of coating thinned to the manufacturer's maximum recommendation, including the volume of any water and exempt compounds. Calculate the VOC content using equation 6 as follows:

$$\text{VOC Content}_{1s} = \frac{(W_s - W_w - W_{ec})}{(V_m)} \quad (6)$$

Where:

VOC content  $_{1s}$  = the VOC content of a low solids coating in grams of VOC per liter of coating

$W_s$  = weight of volatiles, in grams

$W_w$  = weight of water, in grams

$W_{ec}$  = weight of exempt compounds, in grams

$V_m$  = volume of coating, in liters

(3) For recycled coatings, the manufacturer or importer has the option of calculating an adjusted VOC content to account for the post-consumer coating content. If this option is used, the manufacturer or importer shall determine the adjusted VOC content using equations 7 and 8 as follows:

$$\text{Adjusted VOC Content} = \text{Actual VOC Content} - \left( \text{Actual VOC Content} \left( \frac{\text{Percent Post-consumer Coating}}{100} \right) \right) \quad (7)$$

Where:

Adjusted VOC content = The VOC content assigned to the recycled coating for purposes of complying with the VOC content limits in table 1 of this subpart.

Actual VOC content = The VOC content of the coating as determined using equation 5 in paragraph (a)(1) of this section.

Percent Post-consumer Coating = The volume percent of a recycled coating that is post-consumer coating materials (as determined in equation 8)

$$\text{Percent Post-consumer Coating} = \frac{\text{Volume of Post-consumer Coating}}{(\text{Volume of Post-consumer Coating} + \text{Volume of Virgin Materials})} \times 100 \text{ Percent} \quad (8)$$

Where:

Percent Post-consumer Coating = The volume percent of a recycled coating that is post-consumer coating materials.

Volume of Post-consumer Coating = The volume, in liters, of post-consumer coating materials used in the production of a recycled coating.

Volume of Virgin Materials = The volume, in liters, of virgin coating materials used in the production of a recycled coating.

(b) To determine the composition of a coating in order to perform the calculations in paragraph (a) of this section, the reference method for VOC content is Method 24 of appendix A of 40 CFR part 60, except as provided in paragraphs (c) and (d) of this section.

To determine the VOC content of a coating, the manufacturer or importer may use Method 24 of appendix A of 40 CFR part 60, an alternative method as provided in paragraph (c) of this section, formulation data, or any other reasonable means for predicting that the coating has been formulated as intended (e.g., quality assurance checks, recordkeeping). However, if there are any inconsistencies between the results of a Method 24 test and any other means for determining VOC content, the Method 24 test results will govern, except as provided in paragraph (c) of this section. The Administrator may

require the manufacturer or importer to conduct a Method 24 analysis.

(c) The Administrator may approve, on a case-by-case basis, a manufacturer's or importer's use of an alternative method in lieu of Method 24 for determining the VOC content of coatings if the alternative method is demonstrated to the Administrator's satisfaction to provide results that are acceptable for purposes of determining compliance with this subpart.

(d) Analysis of methacrylate multicomponent coatings used as traffic marking coatings shall be conducted according to the procedures specified in appendix A to this subpart. Appendix A to this subpart is a modification of Method 24 of appendix A of 40 CFR part 60. The modification of Method 24 provided in appendix A to this subpart has not been approved for methacrylate multicomponent coatings used for other purposes than as traffic marking coatings or for other classes of multicomponent coatings.

(e) The Administrator may determine a manufacturer's or importer's compliance with the provisions of this subpart based on information required by this subpart (including the records and reports required by §§ 59.407 and 59.408 of this subpart) or any other information available to the Administrator.

#### § 59.407 Recordkeeping requirements.

(a) Each manufacturer and importer using the provisions of § 59.406(a)(3) of this subpart to determine the VOC content of a recycled coating shall maintain in written or electronic form records of the information specified in paragraphs (a)(1) through (a)(6) of this section for a period of 3 years.

(1) The minimum volume percent post-consumer coating content for each recycled coating.

(2) The volume of post-consumer coating received for recycling.

(3) The volume of post-consumer coating received that was unusable.

(4) The volume of virgin materials.

(5) The volume of the final recycled coating manufactured or imported.

(6) Calculations of the adjusted VOC content as determined using equation 7 in § 59.406(a)(3) of this subpart for each recycled coating.

(b) Each manufacturer and importer using the exceedance fee provisions in § 59.403 of this subpart, as an alternative to achieving the VOC content limits in table 1 of this subpart, shall maintain in written or electronic form the records specified in paragraphs (b)(1) through (b)(7) of this section for a period of 3 years.

(1) A list of the coatings and the associated coating categories in table 1 of this subpart for which the exceedance fee is used.

(2) Calculations of the annual fee for each coating and the total annual fee for all coatings using the procedure in § 59.403 (b) and (c) of this subpart.

(3) The VOC content of each coating in grams of VOC per liter of coating.

(4) The excess VOC content of each coating in grams of VOC per liter of coating.

(5) The total volume of each coating manufactured or imported per calendar year, in liters, including the volume of any water and exempt compounds and excluding the volume of any colorant added to tint bases.

(6) The annual fee for each coating.

(7) The total annual fee for all coatings.

(c) Each manufacturer and importer claiming the tonnage exemption in § 59.404 of this subpart shall maintain in written or electronic form the records specified in paragraphs (c)(1) through (c)(4) of this section for a period of 3 years.

(1) A list of all coatings and associated coating categories in table 1 of this subpart for which the exemption is claimed.

(2) The VOC amount as used in equation 4.

(3) The volume manufactured or imported, in liters, for each coating for which the exemption is claimed for the time period the exemption is claimed.

(4) The total megagrams of VOC contained in each coating for which the exemption is claimed, and for all coatings combined for which the exemption is claimed, for the time period the exemption is claimed, as calculated in § 59.404(b) of this subpart.

[63 FR 48877, Sept. 11, 1998; 64 FR 35001, June 30, 1999]